




3 in. Square Recessed LED Modular Downlight, Trimless, Canless, 1300 Lumens, 5 CCT 2700K~5000K

Model: DA-DL-6C12W



12
WATTS ENERGY

1300
LUMENS

5 CCT
2700K, 3000K, 3500K
4000K, 5000K

DIMMABLE
0~10V/120~277V
TRIAC/120V


PRODUCT SPECIFICATIONS

MODEL	DA-DL-6C12W
MANUFACTURER	MTL LIGHTING
LIGHT TYPE	LED Downlight
LIGHT TYPE	LED MODULAR
SHAPE	Square
QTY PACK SIZE	Single Pack
WATTS	5 Power Tunable: 8W/9W/10W/11W/12W
EFFICACY 5000K/6000K	115LM/W
LUMEN OUTPUT	1300LM(1550LM MAX)
CRI	90
LIFETIME HOURS	50000
DIMMABLE	Yes
ETL LISTED	Yes
SUITABLE FOR	Damp Locations
WIDTH	5.16"
HEIGHT	4.33"
LENGTH	2.94"
WEIGHT	0.5KG
VOLTAGE	120V AC
WARRANTY	5 Years
COLOR	White

ADDITIONAL INFORMATION

- 5 CCT Select 2700K/3000K/3500K/4000K/5000K (switch on the driver)
- High CRI rating (90) provides the most accurate appearance of colors in the room
- No ceiling can or housing required
- Power Supply / Junction Box included
- Recommended hole cutout diameter: 3"
- J-Box Dimensions: Triac (6.10"L x 1.42" W x 1.42"H) / 0~10V (3.94"L x 2.68"W x 1.38"H)
- Trim size: 0.35"
- Die-casting Aluminum Body
- Beam angle: 15°/24°/36°
- Dimming range: 5% - 100%
- Aluminum housing acting as the heat sink to maximize life
- 10.63" installation cord from LED Modular to J-Box
- Operating temperature: -4°F to 104°F

SQUARE TRIMLESS DIMENSION



Square Trimless

OTHER OPTIONAL TRIMS




Adjustable Round Trim
Ø3.94"
Ø2.95"~3.03"cutout



Square Trim
Ø3.31"
Ø2.68"~2.85"cutout



Adjustable SquareTrim
Ø3.94"
Ø2.95"~3.03"cutout



Round Trim
Ø3.31"
Ø2.68"~2.85"cutout

Round Trim